

## 2MP 22x IR PTZ Camera



- 1/2.8" SONY Starvis Back-illuminated CMOS Sensor
- H.264/H.265
- 22x Optical Zoom
- IR distance up to 250m
- IR66 Waterproof

### Specifications

Model	OTR10G12L200
<b>Camera</b>	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP
Effective Pixels	1920(H)*1080(V)
Compression	H.264/H.265
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	200° /S
Horizontal Rotation Range	0° -360°
Tilt Rotation Speed	100° /S
Tilt Rotation Range	0° -93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	3.9mm -85.5mm
Focus Control	22x Optical Zoom
<b>Night Vision</b>	
Infrared LED	Φ 42 x 11PCS IR LEDS + 4PCS LED Laser
IR Range	250m
Day-night mode	AUTO
<b>Network</b>	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA

Main Stream 1	1920*1080@30fps
Main Stream 2	1280*960@30fps
Main Stream 3	1280*720@30fps
Main Stream 4	720*576@30fps
Main Stream 5	720*480@30fps
Main Stream 6	640*480@30fps
Sub Stream 1	640**480@30fps
Sub Stream 2	480*360@30fps
Sub Stream 3	352*288@30fps
Sub Stream 4	320*240@30fps
<b>Interface</b>	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	/
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0° ~ +40°    Outdoor: -40° ~ +60°
Operating Humidity	≤90% Non-Condensing
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	33 x 33 x 52 (cm)
Weight	13.7 kgs