

2MP 18x IR PTZ Camera



- 1/2.8" SONY Low Illuminated CMOS Sensor
- H.264/H.264+/H.265/MJPEG
- 18x Optical Zoom
- IR distance up to 60m
- IR66 Waterproof

Specifications

Model	OTR4A18L200
Camera	
Image Sensor	1/2.8" SONY Low Illuminated CMOS Sensor
Resolution	2MP
Effective Pixels	1920(H)*1080(V)
Compression	H.264/H.264+/H.265/MJPEG
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	120° /S
Horizontal Rotation Range	0° -360°
Tilt Rotation Speed	30° /S
Tilt Rotation Range	0° -93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	5.35mm - 96.3mm
Focus Control	18x Optical Zoom
Night Vision	
Infrared LED	30μ x 6PCS
IR Range	60m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA

Main Stream 1	1920*1080@30fps
Main Stream 2	1280*720@30fps
Sub Stream 1	800*448@30fps
Sub Stream 2	704*576@30fps
Sub Stream 3	640*360@30fps
Sub Stream 4	352*288@30fps
AI Function	
Smart Analytic	3D Human Tracking 、 Intrusion Detection 、 Alarm Detection
Tracking effective range	5 - 45M Speed: 3-12KM/h
Interface	
Audio	2-Way Audio
Alarm	/
SD Card Slot	/
POE	Optional
General	
Weatherproof	IP66
Operating Temperature	-40° ~ +70°
Operating Humidity	≤90% Non-Condensing
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	18.5 x 18.5 x 28.8 (cm)
Weight	2.2 kgs