

## 2MP 4x IR PTZ Camera



- 1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
- H.264/H.265
- 4x Optical Zoom
- IR distance up to 80m
- IR66 Waterproof

### Specifications

Model	OTR4XHSL200
<b>Camera</b>	
Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
Resolution	2MP
Effective Pixels	1920(H)*1080(V)
Compression	H.264/H.265
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	30° /S
Horizontal Rotation Range	0° - 180°
Tilt Rotation Speed	25° /S
Tilt Rotation Range	-45° -40°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max. 16 points
<b>Lens</b>	
Focus Length	2.8mm -12mm
Focus Control	4x Optical Zoom
<b>Night Vision</b>	
Infrared LED	35μ × 6PCS
IR Range	80m
Day-night mode	AUTO
<b>Network</b>	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA

Main Stream 1	2304*1296@20fps
Main Stream 2	1920*1080@30fps
Sub Stream 1	800*448@30fps
Sub Stream 2	704*576@30fps
Sub Stream 3	640*360@30fps
Sub Stream 4	352*288@30fps
<b>Interface</b>	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0° ~ +40°    Outdoor: -40° ~ +60°
Operating Humidity	≤90% Non-Condensing
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	39.6 x 19.6 x 16 (cm)
Weight	3 kgs