

2MP 22x IR PTZ Camera



- 1/2.8" SONY Starvis Back-illuminated CMOS Sensor
- H.264/H.265
- 22x Optical Zoom
- IR distance up to 150m
- IR66 Waterproof

Specifications

Model	OTR5E12L200
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP
Effective Pixels	1920(H)*1080(V)
Compression	H.264/H.265
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	120° /S
Horizontal Rotation Range	0° -360°
Tilt Rotation Speed	60° /S
Tilt Rotation Range	0° -93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	3.9mm -85.5mm
Focus Control	22x Optical Zoom
Night Vision	
Infrared LED	7PCS Array IR LEDS + 2PCS Laser Lamp
IR Range	150m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA

Main Stream 1	2304*1296@20fps
Main Stream 2	1920*1080@30fps
Sub Stream 1	800*448@30fps
Sub Stream 2	704*576@30fps
Sub Stream 3	640*360@30fps
Sub Stream 4	352*288@30fps
Interface	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	/
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0° ~ +40° Outdoor: -40° ~ +60°
Operating Humidity	≤90% Non-Condensing
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	25 x 21.5 x 41 (cm)
Weight	4.9 kgs