



# BULLET CAMERA

## 2MP NETWORK CAMERA

OTR2FG200WH



- 1/2.9" Progressive Scan CMOS Sensor
- 3.6 mm Fixed Lens
- Support warm light LED 4000K, up to 25m
- Resolution : 1920 X1080
- Power Source : DC12V  $\pm$  10%, 1000mA
- Dimension : 171(W) x 73(H) x 73(D) mm
- Weight : 750 g



Scan the QR code to view the detailed specifications

- 1/2.9" Progressive Scan CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42 $\mu$  x 2pcs, up to 25m
- Resolution : 1920 X1080
- Power Source : DC12V  $\pm$  10%, 700mA
- Dimension : 70(W) x 67.5(H) x 169(D) mm
- Weight : 600 g



Scan the QR code to view the detailed specifications

OTRCFG200



- 1/2.9" Progressive Scan CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 14 $\mu$  x 20pcs, up to 25m
- Resolution : 1920 X1080
- Power Source : DC12V  $\pm$  10%, 900mA
- Dimension : 158(W) x 76(H) x 73(D) mm
- Weight : 650g

OTR30FG200



Scan the QR code to view the detailed specifications

# BULLET CAMERA

## 2MP NETWORK CAMERA

OTR60FG200



- 1/2.9" Progressive Scan CMOS Sensor
- Lens Length : 2.8-12 mm
- IR LEDs : 42μ x 4pcs, up to 40m
- Resolution : 1920 X1080
- Power Source : DC12V ± 10%, 950mA
- Dimension : 211(W) x 92(H) x 90(D) mm
- Weight : 1.4 kg



Scan the QR code to view  
the detailed specifications

- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42μ x 6pcs, up to 60m
- Resolution : 1920 X1080
- Power Source : DC12V ± 10%, 1100mA
- Dimension : 220(W) x 109(H) x 106(D) mm
- Weight : 2.15 kg



Scan the QR code to view  
the detailed specifications

OTRLARL200



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 6 mm Fixed Lens
- IR LEDs : 42μ x 4pcs, up to 40m
- Resolution : 1920 X1080
- Power Source : DC12V ± 10%, 950mA
- Dimension : 220(W) x 105(H) x 109(D) mm
- Weight : 2.15 kg



Scan the QR code to view  
the detailed specifications

OTRBSL200



# BULLET CAMERA

## 2MP NETWORK CAMERA

OTRESL200



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 6 mm Fixed Lens
- IR LEDs : 42μ x 4pcs, up to 40m
- Resolution : 1920 X1080
- Power Source : DC12V ± 10%, 950mA
- Dimension : 179(W) x 90(H) x 90(D) mm
- Weight : 1.65 kg



Scan the QR code to view  
the detailed specifications

- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42μ x 2pcs, up to 25m
- Resolution : 1920 X1080
- Power Source : DC12V ± 10%, 700mA
- Dimension : 171(W) x 73(H) x 73(D) mm
- Weight : 750 kg



Scan the QR code to view  
the detailed specifications

OTRSARL200



# BULLET CAMERA

## 4MP NETWORK CAMERA

OTRCFG400



- 1/3" Progressive Scan CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42μ x 2pcs, up to 25m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 700mA
- Dimension : 70(W) x 67.5(H) x 169(D) mm
- Weight : 600 g



Scan the QR code to view the detailed specifications

- 1/3" Progressive Scan CMOS Sensor
- 3.6 mm Fixed Lens
- Support warm light LED 4000K, up to 40m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 1000mA
- Dimension : 268(W) x 95(H) x 88(D) mm
- Weight : 1.5 kg



Scan the QR code to view the detailed specifications

OTRBFG400



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42μ x 6pcs, up to 60m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 1100mA
- Dimension : 220(W) x 109(H) x 106(D) mm
- Weight : 2.15 kg



Scan the QR code to view the detailed specifications

OTRLARL400



# BULLET CAMERA

## 4MP NETWORK CAMERA

OTRBSL500



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 6 mm Fixed Lens
- IR LEDs : 42μ x 4pcs, up to 40m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 950mA
- Dimension : 220(W) x 105(H) x 109(D) mm
- Weight : 2.15 kg



Scan the QR code to view the detailed specifications

- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 6 mm Fixed Lens
- IR LEDs : 42μ x 4pcs, up to 40m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 950mA
- Dimension : 179(W) x 90(H) x 90(D) mm
- Weight : 1.65 kg



Scan the QR code to view the detailed specifications

OTRESL500



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42μ x 2pcs, up to 25m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 700mA
- Dimension : 171(W) x 73(H) x 73(D) mm
- Weight : 750 kg



Scan the QR code to view the detailed specifications

OTRSARL400



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42μ x 2pcs, up to 25m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 700mA
- Dimension : 171(W) x 73(H) x 73(D) mm
- Weight : 750 kg



Scan the QR code to view the detailed specifications

# BULLET CAMERA

## 8MP NETWORK CAMERA

OTRESL800



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 6 mm Fixed Lens
- IR LEDs : 42 $\mu$  x 4pcs, up to 40m
- Resolution : 3840 x 2160
- Power Source : DC12V  $\pm$  10%, 950mA
- Dimension : 179(W) x 90(H) x 90(D) mm
- Weight : 1.65 kg



Scan the QR code to view the detailed specifications

- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 6 mm Fixed Lens
- IR LEDs : 42 $\mu$  x 4pcs, up to 40m
- Resolution : 3840 x 2160
- Power Source : DC12V  $\pm$  10%, 950mA
- Dimension : 220(W) x 105(H) x 109(D) mm
- Weight : 2.15 kg



Scan the QR code to view the detailed specifications

OTRBSL800



# DOME CAMERA

## 2MP NETWORK CAMERA

OTRDBAFG200



- 1/2.9" Progressive Scan CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 14 $\mu$  x 18pcs, up to 20m
- Resolution : 1920 X1080
- Power Source : DC12V  $\pm$  10%, 750mA
- Dimension :  $\Phi$  93 x 74(H) mm
- Weight : 400 g



Scan the QR code to view the detailed specifications

- 1/2.9" Progressive Scan CMOS Sensor
- 3.6 mm Fixed Lens
- Support warm light LED 4000K, up to 25m
- Resolution : 1920 X1080
- Power Source : DC12V  $\pm$  10%, 1000mA
- Dimension :  $\Phi$  109 x 93(H) mm
- Weight : 600 g



Scan the QR code to view the detailed specifications

OTRAFG200WH



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42 $\mu$  x 2pcs, up to 25m
- Resolution : 1920 X1080
- Power Source : DC12V  $\pm$  10%, 700mA
- Dimension :  $\Phi$  96 x 91(H) mm
- Weight : 600 g



Scan the QR code to view the detailed specifications

OTRBISL200





# DOME CAMERA

## 2MP NETWORK CAMERA

OTRAIS200



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 6 mm Fixed Lens
- IR LEDs : 42μ x 2pcs, up to 25m
- Resolution : 1920 X1080
- Power Source : DC12V ± 10%, 700mA
- Dimension : Φ 136 x 148(H) mm
- Weight : 1700 g



Scan the QR code to view the detailed specifications

- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42μ x 4pcs, up to 30m
- Resolution : 1920 X1080
- Power Source : DC12V ± 10%, 950mA
- Dimension : Φ 140 x 123(H) mm
- Weight : 1200 g



Scan the QR code to view the detailed specifications

OTRBHL200



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 14μ x 12pcs, up to 20m
- Resolution : 1920 X1080
- Power Source : DC12V ± 10%, 650mA
- Dimension : Φ 110 x 76(H) mm
- Weight : 450 g

OTRHRL200



Scan the QR code to view the detailed specifications

# DOME CAMERA

## 4MP NETWORK CAMERA

OTRAIS500



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 6 mm Fixed Lens
- IR LEDs : 42μ x 2pcs, up to 25m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 700mA
- Dimension : Φ 136 x 148(H) mm
- Weight : 1700 g



Scan the QR code to view the detailed specifications

- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42μ x 4pcs, up to 30m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 950mA
- Dimension : Φ 140 x 123(H) mm
- Weight : 1200 g



Scan the QR code to view the detailed specifications

OTRBHRL400



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 14μ x 12pcs, up to 20m
- Resolution : 2688 x 1520
- Power Source : DC12V ± 10%, 650mA
- Dimension : Φ 110 x 76(H) mm
- Weight : 450 g



Scan the QR code to view the detailed specifications

OTRHRL400



# DOME CAMERA

## 4MP NETWORK CAMERA

OTRAFG400WH



- 1/3" Progressive Scan CMOS Sensor
- 3.6 mm Fixed Lens
- Support warm light LED 4000K, up to 25m
- Resolution : 2688 x 1520
- Power Source : DC12V  $\pm$  10%, 1000mA
- Dimension :  $\Phi$  109 x 93(H) mm
- Weight : 600 g



Scan the QR code to view  
the detailed specifications

- 1/2.8" Starvis Back-illuminated CMOS Sensor
- Lens Length : 2.7-13.5 mm
- IR LEDs : 42 $\mu$  x 4pcs, up to 30m
- Resolution : 2688 x 1520
- Power Source : DC12V  $\pm$  10%, 950mA
- Dimension :  $\Phi$  140 x 123(H) mm
- Weight : 1200 g



Scan the QR code to view  
the detailed specifications

OTR5XRL400



# DOME CAMERA

## 8MP NETWORK CAMERA

OTRAIS800



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 6 mm Fixed Lens
- IR LEDs : 42μ x 2pcs, up to 25m
- Resolution : 3840 x 2160
- Power Source : DC12V ± 10%, 700mA
- Dimension : Φ 136 x 148(H) mm
- Weight : 1700 g



Scan the QR code to view  
the detailed specifications

- 1/2.8" Starvis Back-illuminated CMOS Sensor
- 3.6 mm Fixed Lens
- IR LEDs : 42μ x 2pcs, up to 25m
- Resolution : 3840 x 2160
- Power Source : DC12V ± 10%, 700mA
- Dimension : Φ 96 x 91(H) mm
- Weight : 600 g



Scan the QR code to view  
the detailed specifications

OTRBISL800



# PTZ CAMERA

## 2MP NETWORK CAMERA

OTR6A18L200



- 1/2.8" Low Illuminated CMOS Sensor
- IR LEDs :  $\phi$  42 x 6pcs IR Lens + 2pcs Laser LED
- IR Range : 120m
- Resolution : 1920 X1080
- Focus Length : 5.35mm-96.3mm
- Focus Control : 18X Optical Zoom
- Power Source : DC12V, 4A
- Dimension : 255(W) x 215(H) x 410(D) mm
- Weight : 3.1 kg



Scan the QR code to view  
the detailed specifications

- 1/2.8" Starvis Back-illuminated CMOS Sensor
- IR LEDs :  $\phi$  42 x 6pcs
- IR Range : 120m
- Resolution : 1920 X1080
- Focus Length : 3.9mm-85.5mm
- Focus Control : 22X Optical Zoom
- Power Source : DC12V, 2A / 3A
- Dimension : 295(W) x 280(H) x 170(D) mm
- Weight : 4.2 kg



Scan the QR code to view  
the detailed specifications

OTR5A22L200



OTR4A18L200



- 1/2.8" Low Illuminated CMOS Sensor
- IR LEDs : 30 $\mu$  x 6pcs
- IR Range : 60m
- Resolution : 1920 X1080
- Focus Length : 5.35mm-96.3mm
- Focus Control : 18X Optical Zoom
- Power Source : DC12V, 3A
- Dimension : 185(W) x 185(H) x 288(D) mm
- Weight : 2.2 kg



Scan the QR code to view  
the detailed specifications

# PTZ CAMERA

## 2MP NETWORK CAMERA

OTR10G12L200



- 1/2.8" Starvis Back-Illuminated CMOS Sensor
- IR LEDs :  $\phi$  42 x 11pcs IR Lens + 4pcs Laser LED
- IR Range : 250m
- Resolution : 1920 X1080
- Focus Length : 3.9mm-85.5mm
- Focus Control : 22X Optical Zoom
- Power Source : DC12V, 4A
- Dimension : 330(W) x 330(H) x 520(D) mm
- Weight : 13.7 kg



Scan the QR code to view  
the detailed specifications

- 1/2.8" Starvis Back-Illuminated CMOS Sensor
- IR LEDs :  $\phi$  42 x 6pcs IR Lens + 2pcs Laser LED
- IR Range : 120m
- Resolution : 1920 X1080
- Focus Length : 3.9mm-85.5mm
- Focus Control : 22X Optical Zoom
- Power Source : DC12V, 4A
- Dimension : 310(W) x 310(H) x 440(D) mm
- Weight : 10.7 kg



Scan the QR code to view  
the detailed specifications

OTR7K12L200



OTR5E12L200



- 1/2.8" Starvis Back-Illuminated CMOS Sensor
- IR LEDs : 7pcs Array IR Lens + 2pcs Laser Lamp
- IR Range : 150m
- Resolution : 1920 X1080
- Focus Length : 3.9mm-85.5mm
- Focus Control : 22X Optical Zoom
- Power Source : DC12V, 2A /3A
- Dimension : 250(W) x 215(H) x 410(D) mm
- Weight : 4.9 kg



Scan the QR code to view  
the detailed specifications

# PTZ CAMERA

## 2MP NETWORK CAMERA

OTR4XHSL200



- 1/2.9" Low Illuminated 2.1MP CMOS Sensor
- IR LEDs : 35 $\mu$  x 6pcs
- IR Range : 80m
- Resolution : 1920 X1080
- Focus Length : 2.8mm-12mm
- Focus Control : 4X Optical Zoom
- Power Source : DC12V, 3A
- Dimension : 396(W) x 196(H) x 160(D) mm
- Weight : 3 kg



Scan the QR code to view  
the detailed specifications

- 1/2.9" Low Illuminated 2.1MP CMOS Sensor
- IR LEDs : 4pcs Array IR Lens + 2pcs Laser Lamp
- IR Range : 100m
- Resolution : 1920 X1080
- Focus Length : 5.1mm-51mm
- Focus Control : 10X Optical Zoom
- Power Source : DC12V, 3A
- Dimension : 396(W) x 196(H) x 160(D) mm
- Weight : 3 kg



Scan the QR code to view  
the detailed specifications

OTR10XHSL200



# PTZ CAMERA

## 5MP NETWORK CAMERA

OTR7K12S500



- 1/2.8" Starvis Back-Illuminated CMOS Sensor
- IR LEDs :  $\phi$  42 x 6pcs IR Lens + 2pcs Laser LED
- IR Range : 120m
- Resolution : 5MP
- Focus Length : 4.7mm-94mm
- Focus Control : 20X Optical Zoom
- Power Source : DC12V, 4A
- Dimension : 310(W) x 310(H) x 440(D) mm
- Weight : 10.7 kg



Scan the QR code to view the detailed specifications

- 1/2.8" Starvis Back-Illuminated CMOS Sensor
- IR LEDs :  $\phi$  42 x 6pcs IR Lens + 2pcs Laser LED
- IR Range : 120m
- Resolution : 5MP
- Focus Length : 4.6mm-165mm
- Focus Control : 36X Optical Zoom
- Power Source : DC12V, 4A
- Dimension : 310(W) x 310(H) x 440(D) mm
- Weight : 10.7 kg



Scan the QR code to view the detailed specifications

OTR7K13S500



OTR5A22S500



- 1/2.8" Starvis Back-illuminated CMOS Sensor
- IR LEDs :  $\phi$  42 x 6pcs
- IR Range : 120m
- Resolution : 5MP
- Focus Length : 3.9mm-85.5mm
- Focus Control : 22X Optical Zoom
- Power Source : DC12V, 2A / 3A
- Dimension : 295(W) x 280(H) x 170(D) mm
- Weight : 4.2 kg



Scan the QR code to view the detailed specifications



# PTZ CAMERA

## 5MP NETWORK CAMERA

OTR5E12S500



- 1/2.8" Starvis Back-Illuminated CMOS Sensor
- IR LEDs : 7pcs Array IR Lens + 2pcs Laser Lamp
- IR Range : 150m
- Resolution : 2560 x 1920
- Focus Length : 3.9mm-85.5mm
- Focus Control : 22X Optical Zoom
- Power Source : DC12V, 2A /3A
- Dimension : 250(W) x 215(H) x 410(D) mm
- Weight : 4.9 kg



Scan the QR code to view  
the detailed specifications

- 1/2.8" Starvis Back-Illuminated CMOS Sensor
- IR LEDs : 35μ x 6pcs
- IR Range : 80m
- Resolution : 2560 x 1920
- Focus Length : 2.8mm-12mm
- Focus Control : 4X Optical Zoom
- Power Source : DC12V, 3A
- Dimension : 396(W) x 196(H) x 160(D) mm
- Weight : 3 kg



Scan the QR code to view  
the detailed specifications

OTR4XSS500



OTR10XSS500



- 1/2.8" Starvis Back-Illuminated CMOS Sensor
- IR LEDs : 4pcs Array IR Lens + 2pcs Laser Lamp
- IR Range : 100m
- Resolution : 2560 x 1920
- Focus Length : 5.1mm-51mm
- Focus Control : 10X Optical Zoom
- Power Source : DC12V, 3A
- Dimension : 396(W) x 196(H) x 160(D) mm
- Weight : 3 kg



Scan the QR code to view  
the detailed specifications

# NETWORK VIDEO RECORDER

## OTR2104



- 9 Channel
- 1 SATA Hard Disk Interface (3.5" SATA)
- Up to 8TB capacity
- 2 USB 2.0 Interfaces
- Power Source : DC52V, 1250mA
- Dimension : 260(W) x 215(H) x 43(D) mm
- Weight : 2 kg




Scan the QR code to view the detailed specifications

- 9 Channel
- 1 SATA Hard Disk Interface (3.5" SATA)
- Up to 8TB capacity
- 2 USB 2.0 Interfaces
- Power Source : DC12V, 2A
- Dimension : 260(W) x 215(H) x 43(D) mm
- Weight : 2 kg




Scan the QR code to view the detailed specifications

## OTR2109



## OTR3004



- 9 Channel
- 1 SATA Hard Disk Interface (3.5" SATA)
- Up to 8TB capacity
- 2 USB 2.0 Interfaces
- Power Source : DC52V, 1250mA
- Dimension : 260(W) x 215(H) x 43(D) mm
- Weight : 2 kg



Scan the QR code to view the detailed specifications

# NETWORK VIDEO RECORDER

## OTR3016



- 16 Channel
- 1 SATA Hard Disk Interface (3.5" SATA)
- Up to 8TB capacity
- 2 USB 2.0 Interfaces
- Power Source : DC12V, 2A
- Dimension : 260(W) x 215(H) x 43(D) mm
- Weight : 2 kg




Scan the QR code to view the detailed specifications

- 16 Channel
- 1 SATA Hard Disk Interface (3.5" SATA)
- Up to 8TB capacity
- 2 USB 2.0 Interfaces
- Power Source : DC12V, 2A
- Dimension : 260(W) x 215(H) x 43(D) mm
- Weight : 2 kg



Scan the QR code to view the detailed specifications

## OTR2116



## OTR2108



- 16 Channel
- 1 SATA Hard Disk Interface (3.5" SATA)
- Up to 8TB capacity
- 2 USB 2.0 Interfaces
- Power Source : DC52V, 2500mA
- Dimension : 260(W) x 215(H) x 43(D) mm
- Weight : 2 kg



Scan the QR code to view the detailed specifications

# NETWORK VIDEO RECORDER

## OTR3008



- 16 Channel
- 1 SATA Hard Disk Interface (3.5" SATA)
- Up to 8TB capacity
- 2 USB 2.0 Interfaces
- Power Source : DC52V, 2500mA
- Dimension : 260(W) x 215(H) x 43(D) mm
- Weight : 2 kg



Scan the QR code to view the detailed specifications

- 64 Channel
- 8 SATA Hard Disk Interface (3.5" SATA)
- Up to 48TB capacity
- 1 eSATA interface
- 2 USB 2.0 Interfaces, 1 USB 3.0 Interface
- Power Source : AC 115 to 230V, 3A
- Dimension : 440(W) x 450(H) x 95(D) mm
- Weight : 9.8 kg



Scan the QR code to view the detailed specifications

## OTR3664



# NETWORK POE SWITCH

## OTR412



- Input : 110-240V/AC 50-60Hz
- Maximum power supply : 60W
- 1-4 port : 10/100Mbps PoE Ethernet LAN port
- WAN1/2 port : 10/100Mbps Ethernet WAN port
- Dimension : 220(W) x 140(H) x 40(D) mm
- Weight : 1.1 kg



Scan the QR code to view the detailed specifications

- Input : 110-240V/AC 50-60Hz 5
- Maximum power supply : 100W
- 1-8 port : 10/100Mbps PoE Ethernet LAN port
- WAN port : 10/100Mbps Ethernet WAN port
- Dimension : 220(W) x 140(H) x 40(D) mm
- Weight : 1.1 kg

## OTR811



Scan the QR code to view the detailed specifications

## OTR81M2



- Input : 110-240V/AC 50-60Hz 5
- Maximum power supply : 100W
- 1-8 port : 10/100Mbps PoE Ethernet LAN port
- WAN1/2 port : 10/100Mbps Ethernet WAN port
- Dimension : 220(W) x 140(H) x 40(D) mm
- Weight : 1.4 kg



Scan the QR code to view the detailed specifications

# NETWORK POE SWITCH

## OTR812



- Input : 110-240V/AC 50-60Hz 5
- Maximum power supply : 100W
- 1-8 port : 10/100Mbps PoE Ethernet LAN port
- WAN1/2 port : 10/100/1000 Mbps Ethernet WAN port
- Dimension : 220(W) x 140(H) x 40(D) mm
- Weight : 1.4 kg



Scan the QR code to view the detailed specifications

- Input : 110-240V/AC 50/60Hz
- Maximum power supply : 240W
- 1-16 port : 10/100Mbps PoE Ethernet port
- WAN1/2 port : 10/100/1000Mbps
- Dimension : 290(W) x 200(H) x 44(D) mm
- Weight : 3.5 kg



Scan the QR code to view the detailed specifications

## OTR1612



- Input : 100-240V/AC 50/60Hz
- Maximum power supply : 440W
- 1-24 port : 10/100Mbps PoE Ethernet port
- 25-28 port : 10/100/1000Mbps WAN1/2 port
- Dimension : 441(W) x 300(H) x 44(D) mm
- Weight : 5.3 kg

## OTR2418



Scan the QR code to view the detailed specifications



[www.otron.com.hk](http://www.otron.com.hk)