

OTR1612



Power	
Power Adapter Voltage	Input : 100-240V/AC 50/60Hz
The maximum power supply machine	240W
Protection level	
Mould	+ - 4KV
Differential mode	+ - 1KV
Network Connector	
Network Port	1~16 port : 10/100Mbps PoE Ethernet port WAN1 / WAN2 port :10/100/1000Mbps
Transmission Distance	Extend switch is default OFF, state (1~16 port) : 100m Extend switch is ON, state : (1~16 port:) : 250m WAN1 / WAN2 port : 100m
Transmission Medium	Cat5 / 5e / 6 standard network cable
Network Switch	
Network Standard	IEEE802.3/10BASE-T IEEE802.3u/100BASE-TX IEEE802.3x Flow Control, IEEE802.3az
Maximum Frame Size	1536 Bytes
MAC address lis	2K
Backplane bandwidth	1Gbps
PoE Standard	IEEE802.3af / at
Power Over Ethernet	
PoE Power Supply Type	End-Span(4/5+;7/8-)
PoE Power Consumption	af, at Adaptive (every port)
LED Status Indicator	
PoE Ethernet	When the PoE is powered, 1-16 LEDs are green When accessing Ethernet, ports 1-16 are yellow
Environmental	
Working temperature	0°C~55°C
Storage temperature	-40°C~70°C
Working humidity	10% - 90% non-condensing
Storage humidity	5% - 95% RH non-condensing
Mechanical	
Dimension (L x W x H) mm	290*200*44
Weight	3.5KG
Material	SECC
Color	Dark grey
Stability	
MTBF	>30000h