

OTR4A18L200



Camera	
Image Sensor	1/2.8" Low Illumination CMOS Sensor
Resolution	2MP
Compression	H.264/H.264+/H.265/MJPEG
S/N Ratio	>50db

PTZ	
Horizontal Rotation Speed	120° / S
Horizontal Rotation Range	0° ~ 360°
Tilt Rotation Speed	30° / S
Tilt Rotation Range	0° ~ 93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max. 16 points

Lens	
Focus Length	5.35mm – 96.3mm
Focus Control	18X Optical Zoom

Night Vision	
Infrared LED	30μx6PCS
IR Range	60m
Day-night mode	AUTO

AI Function	
Smart Analytic	3D Human Tracking, Intrusion Detection, Alarm Detection
Tracking effective range	5 ~ 45M Speed: 3 ~ 12KM/h

Interface	
Audio	2-Way Audio
Alarm	/
SD Card Slot	/
POE	Optional

Network	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA
Main Stream 1	1920*1080@30fps
Main Stream 2	1280*720@30fps
Sub Stream 1	800*448@30fps
Sub Stream 2	704*576@30fps
Sub Stream 3	640*360@30fps
Sub Stream 4	352*288@30fps

General	
Weatherproof	IP66
Operating Temperature	-40°C ~ +70°C
Operation Humidity	≤90% Non Condensing
Power	DC12V / 3A
Lightning Protection	Transient voltage 6000V
Dimension	18.5 X 18.5 X 28.8 (cm)
Weight	2.2Kgs