

# OTR5A22L200



<b>Camera</b>	
Image Sensor	1/2.8" Starvis Back-Illumination CMOS Sensor
Resolution	2MP
Compression	H.265/H.264
S/N Ratio	>50db

<b>PTZ</b>	
Horizontal Rotation Speed	45 ° / S
Horizontal Rotation Range	0 ° ~ 360 °
Tilt Rotation Speed	30 ° / S
Tilt Rotation Range	0 ° ~ 93 °
Preset Points	220
Guard Tours	3 groups
Guard Points	Max. 16 points

<b>Lens</b>	
Focus Length	3.9mm – 85.5mm
Focus Control	22X Optical Zoom

<b>Night Vision</b>	
Infrared LED	ϕ 42x6PCS
IR Range	120m
Day-night mode	AUTO

<b>Interface</b>	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional

<b>Network</b>	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA
Main Stream 1	2304*1296@20fps
Main Stream 2	1920*1080@30fps
Sub Stream 1	800*448@30fps
Sub Stream 2	704*576@30fps
Sub Stream 3	640*360@30fps
Sub Stream 4	352*288@30fps

<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0° ~ +40° Outdoor: -40° ~ +60°
Operation Humidity	≤90% Non Condensing
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	29.5 X 28 X 17 (cm)
Weight	4.2 kg