

OTR5E12L200



Camera	
Image Sensor	1/2.8" Starvis Back-Illumination CMOS Sensor
Resolution	2MP
Compression	H.265/H.264
S/N Ratio	>50db

PTZ	
Horizontal Rotation Speed	120° / S
Horizontal Rotation Range	0° ~ 360°
Tilt Rotation Speed	60° / S
Tilt Rotation Range	0° ~ 93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max. 16 points

Lens	
Focus Length	3.9mm – 85.5mm
Focus Control	22X Optical Zoom

Night Vision	
Infrared LED	7PCS Array IR LEDS + 2PCS Laser Lamp
IR Range	150m
Day-night mode	AUTO

Interface	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	/

Network	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA
Main Stream 1	2304*1296@20fps
Main Stream 2	1920*1080@30fps
Sub Stream 1	800*448@30fps
Sub Stream 2	704*576@30fps
Sub Stream 3	640*360@30fps
Sub Stream 4	352*288@30fps

General	
Weatherproof	IP66
Operating Temperature	Indoor: 0° ~ +40° Outdoor: -40° ~ +60°
Operation Humidity	≤90% Non Condensing
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	25 X 21.5 X 41 (cm)
Weight	4.9Kgs