

OTR7K13S500



Camera	
Image Sensor	1/2.8" Starvis Back-Illumination CMOS Sensor
Resolution	5MP
Compression	H.265/H.264
S/N Ratio	>50db

PTZ	
Horizontal Rotation Speed	120 ° / S
Horizontal Rotation Range	0 ° ~ 360 °
Tilt Rotation Speed	30 ° / S
Tilt Rotation Range	0 ° ~ 93 °
Preset Points	220
Guard Tours	3 groups
Guard Points	Max. 16 points

Lens	
Focus Length	4.6mm – 165mm
Focus Control	36X Optical Zoom

Night Vision	
Infrared LED	∅ 42 x 6PCS IR LEDS + 2PCS Laser LED
IR Range	120m
Day-night mode	AUTO

Interface	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional

Network	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA
Main Stream 1	2560*1920@20fps
Main Stream 2	2560*1440@25fps
Main Stream 3	2304*1296@25fps
Main Stream 4	1920*1080@25fps
Main Stream 5	1280*720@25fps
Main Stream 6	640*512@25fps
Sub Stream 1	800*448@25fps
Sub Stream 2	704*576@25fps
Sub Stream 3	640*360@25fps
Sub Stream 4	352*288@25fps

General	
Weatherproof	IP66
Operating Temperature	Indoor: 0° ~ +40° Outdoor: -40° ~ +60°
Operation Humidity	≤90% Non Condensing
Power	DC12V / 4A
Lightning Protection	Transient voltage 6000V
Dimension	31 X 31 X 44 (cm)
Weight	10.7 kg