

4MP(2K) IR IK10 IP67 POE Network Dome Camera



- IR POE Dome Camera
- Fixed-focal (3.6mm)
- H.265/H.264
- 2688*1522 Mainstream resolution
- Support body detection & human frame
- IK10, IP67

Specifications

Model	OTRARG400WHDI
Camera	
Image Sensor	1/3" 4MP CMOS Sensor
Resolution	4MP
Effective Pixels	2688(H)*1522(V)
Lens	3.6mm
Compression	H.265/H.264
LUX	Color 0.05Lux@F1.2; B&W 0.005Lux@F1.2
S/N	≥50db(AGC OFF)
WDR	DWDR: >80db
Audio	
Audio/Intercom Input	Audio MIC Input (optional)
Audio Output	Built-in power magnify circuit
LED Type	CDS IR / Sensor Control / Warm LED / Extra add LED drive board (Optional)
Other Function	IRCUT, Reset
Extension Function	Extension with IO
Network	
Main Stream	2560*1440, 1-25fps/s
	2304*1296、1920*1080、1280*720,1-30fps/s
Sub Stream	704*576、640*480、640*360、352*288,1-30fps/s
Video Coding Compression	128Kbps-8192bps Continuous Adjustable
Subtitle Overlay	Support Channel Name & Data & Time & Frame & Resolution & 4 Lines of Character Overlay
Data Transmission & Storage	
Data Record	Video & Picture
Storage Method	Cycling Recording & Alarm Recording
Alarm Transfer	Brower & Management Software, App
Protocol	ONVIF

Browser	Support IE Brower & Management Software Viewing
Mobile	WANAN App/IOS/Android
Technical Specifications	
Temperature	-30°C ~ +60°C
Humidity	0% - 90%
Protection	IK10, IP67
Power	DC12V/150mA
Consumption	< 2W